

Calkins Chisel Chopper TM



The Calkins Chisel Chopper can save time, fuel, and money by eliminating several other field operations which also reduces ground compaction. The Chisel Chopper mixes surface residue into the soil to speed decomposition and opens up the ground for better water absorption while reducing wind and water erosion of valuable top soil.

Features:

■ **MAINFRAME:** Our rugged four-bar frame design is constructed with 6"x4" steel tubing, offering better placement of the shank for more trash clearance.

■ **WHEEL LEG ASSEMBLY:** Walking beams have replaceable spindles, heavy-duty 8-bolt hubs, tapered bearings on walking beam pivot, and wheels. Tandem walking wheels support more weight and add stability in road transport position.

■ **FRONT ATTACHMENT:** 20" coulters on 12" spacing or paddle gangs. The front attachment with hydraulic in or out as needed for field conditions. The front attachment comes with hydraulic lift and is spring-loaded for easy adjustment to any soil condition.

■ **SHANKS:** The 1-1/4"x 2"x 32" spring cushion shank assembly is standard equipment. Four rows of shanks placed on 12"-centers give maximum trash clearance while working the ground completely.

■ **PADDLES:** 28" paddle sections are placed on 30" gangs or 60" gangs. Every paddle section has two heavy-duty, relubeable, sealed bearings; The paddle blade is self-sharpening.

■ **REAR PADDLES:** 5-blade and 6-blade chopper sections are mounted on each 60" paddle gang assembly. This reduces vibration, provides smooth cutting action and increases cutting pressure on the cutting blade. The spring-loaded chopper sections are adjustable to suit soil conditions.



COULTERS



PADDLES

CHISEL CHOPPER SPECIFICATIONS				
Model	13'	15'	17'	20'
NUMBER OF SHANKS	13	15	17	19
WORKING WIDTH,	12'6"	15'6"	17'6"	20'
TRANSPORT LENGTH,	21'8"	21'8"	21'8"	21'8"
TRANSPORT WIDTH,	15'6"	15'6"	17'11"	20'5"
TRANSPORT HEIGHT,	7'3"	7'3"	7'3"	7'3"
WEIGHT (LBS),	7,953	8,512	9,630	11,465
SUGGESTED HORSEPOWER:	185-240	225-325	250-375	325-425